

Special Plastic Emulsion

Description

Décor your interiors elegantly with carefully formulated Happilac Plastic Emulsion. Its delicate velvet finish infuses in your mind letting you experience something picture-perfect. Its acrylic based binder gives your wall long lasting coating and exquisite look while retaining the excellent eco-friendly nature. It is a blend of perfection, style and charisma. Get your place updated with Happilac Plastic Emulsion.

Recommended For

deal for all interiors from masonry walls to chipboards, hardboards and ceilings. Use Happilac primer for stronger adhesion and increased paint life.

Features

- Excellent Durability and performance
- 100% Acrylic based binder
- Long lasting and high color fastness
- Enriched with appealing perfume
- Quick drying
- Easy application and clean up
- Eco-friendly and non-toxic

Limitations

- Drying time may vary depending on weather and drying conditions.
- Ensure the correct primer or sealers used.

Product Information

Tint Bases: Happilac Standard Tinters.	Binder type 100% Acrylic Pigment type Titanium dioxide
Color Range: See appropriate shade card.	Volume solids 46±2 % Weight solids 69±2 % Specific gravity 1.47±0.08
Tintolac Machine: With Happilac Tintolac machines, get your happy color instantly from a color palette of 1000+ colors.	Viscosity 10± 2 Poise Flash point Not applicable PH slightly alkaline Application Brush, Roller, Spray Finish Matt
Certifications: VOC compliant in all regulated areas. OHSAS : 18001 ISO : 14001 ISO : 9001	Odor Perfume enriched Thinner Water, Max. 25-40% Dries by Evaporation, Oxidation Surface Dry 20-30 minutes Hard Dry 2-3 hours Recoat 1.5-2 hours
Technical Help: Happilac Paints technical department is always available to assist you in the correct use of our products.	Drying and recoat times are temperature, humidity and film thickness dependent Coverage 12-13 m ² /liter/coat Film thickness 25-30 microns per coat Packing 16 ltr, 4 ltr, 1 ltr Storage temperature 4-33 °C Color Range See appropriate shade card.

Surface Preparation and Application

Appropriate and good surface preparation significantly increases the top coat life and durability. Deploy skilled/experienced individuals for the application of paint. A few general instructions are given below:

New or Bare Surfaces

Surface to be painted must be dry, clean and free from all contamination. Remove dirt, grease and waxy material. Scuff with suitable sand paper, dust off and apply Happilac Wall Primer Sealer. Fill surface imperfections with Happilac Strong Wall Filling and let it complete dry followed by 2-3 coats of Happilac Special Plastic Emulsion.

Previously Painted Surfaces

Remove loosely adherent old paint, clean the surface, rub with suitable sand paper to smooth the surface. Apply one coat of Happilac Wall Pri1-2 coats of Happilac Strong Wall Filling. Ensure the complete drying and apply 2-3 coats of Happilac Special Plastic Emulsion.

Sequence	Recommended Paint System	
	Recommended Product	No. of Coats
Sealer	Happilac Wall Primer Sealer	1
Putty/Filling	Happilac Strong Wall Filling/Happilac Silk Putty	1-2
Finish	Happilac Special Plastic Emulsion	2-3

Health and Safety Notes

- When applying paint, wear appropriate eye protection.
- In case of eye contact with product, rinse with plenty of water for at least 10 minutes.
- Don't breathe spray mist or dust.
- Ensure proper ventilation when applying paint.
- If swallowed, it may cause serious damage.
- When empty, don't use its container for edible storage.
- Place out of reach of the children.
- Pregnant women are advised to avoid breathing of paint mist or spray.
- In case of any emergency, undergo medical supervision as soon as possible.

WARNING: Scraping/sanding off previously painted surfaces may release lead dust or fumes. Lead is highly toxic, take protective measures thoroughly when rubbing off the old surfaces.