

## Paint Remover

### Description

**H**appilac Paint Remover is a fast reactive, slow evaporating and superior quality compound which on application swells the old paint and enables its easy removal.

### Features

- Excellent removing tendency
- Ready to use product
- Suitable for all surfaces

### Recommended For

**H**appilac Paint Remover is used to remove paint from all types of surfaces.

### Limitations

Softening the paint depends upon the thickness of the paint.

### Product Information

<p><b>Certifications:</b></p> <p>VOC compliant in all regulated areas. OHSAS : 18001 ISO : 14001 ISO : 9001</p>	<p><b>Composition</b> Blend of solvents and additives</p> <p><b>Pigment type</b> N/A</p> <p><b>Volume solids</b> N/A</p> <p><b>Weight solids</b> N/A</p> <p><b>Specific gravity</b> 1.02±0.02</p> <p><b>Odor</b> Slightly odor</p> <p><b>Flash point</b> Flammable</p> <p><b>Thinning</b> Not required</p> <p><b>Performance</b> Excellent</p> <p><b>Viscosity</b> Ready to use</p> <p><b>PH</b> Not applicable</p> <p><b>Application</b> Brush, Roller, Spray</p> <p><b>Dries by</b> Evaporation, Oxidation</p> <p><b>Packing</b> 0.91 ltr</p> <p><b>Storage temperature</b> 4-28 °C</p> <p><b>Color</b> Clear</p>
<p><b>Technical Help:</b></p> <p>Happilac Paints technical department is always available to assist you in the correct use of our products.</p>	
<p><b>Storage:</b></p> <p>The product must be stored in cool, dry and well ventilated place away from source of heat and ignition. Keep the container closed and upright.</p>	

### Surface Preparation and Application

Remove dirt and grease from the surface. Apply Happilac Paint Remover with a brush and give enough time for the film to become soft before removing it with a scraper. Softening of the paint depends upon the type of thickness of paint. Do not allow the paint remover to dry on surface. Residues remaining after the scraping of the paint should be carefully removed by scuffing and wash with water. The surface then should thoroughly be dried. In case of wood, it should be left on minimum possible time otherwise it will penetrate into the wood pores and may affect subsequent paint coatings.

## Paint Remover

### Description

**H**appilac Paint Remover is a fast reactive, slow evaporating and superior quality compound which on application swells the old paint and enables its easy removal.

### Features

- Excellent removing tendency
- Ready to use product
- Suitable for all surfaces

### Recommended For

**H**appilac Paint Remover is used to remove paint from all types of surfaces.

### Limitations

Softening the paint depends upon the thickness of the paint.

### Product Information

<p><b>Certifications:</b></p> <p>VOC compliant in all regulated areas. OHSAS : 18001 ISO : 14001 ISO : 9001</p>	<p><b>Composition</b> Blend of solvents and additives</p> <p><b>Pigment type</b> N/A</p> <p><b>Volume solids</b> N/A</p> <p><b>Weight solids</b> N/A</p> <p><b>Specific gravity</b> 1.02±0.02</p> <p><b>Odor</b> Slightly odor</p> <p><b>Flash point</b> Flammable</p> <p><b>Thinning</b> Not required</p> <p><b>Performance</b> Excellent</p> <p><b>Viscosity</b> Ready to use</p> <p><b>PH</b> Not applicable</p> <p><b>Application</b> Brush, Roller, Spray</p> <p><b>Dries by</b> Evaporation, Oxidation</p> <p><b>Packing</b> 0.91 ltr</p> <p><b>Storage temperature</b> 4-28 °C</p> <p><b>Color</b> Clear</p>
<p><b>Technical Help:</b></p> <p>Happilac Paints technical department is always available to assist you in the correct use of our products.</p>	
<p><b>Storage:</b></p> <p>The product must be stored in cool, dry and well ventilated place away from source of heat and ignition. Keep the container closed and upright.</p>	

### Surface Preparation and Application

Remove dirt and grease from the surface. Apply Happilac Paint Remover with a brush and give enough time for the film to become soft before removing it with a scraper. Softening of the paint depends upon the type of thickness of paint. Do not allow the paint remover to dry on surface. Residues remaining after the scraping of the paint should be carefully removed by scuffing and wash with water. The surface then should thoroughly be dried. In case of wood, it should be left on minimum possible time otherwise it will penetrate into the wood pores and may affect subsequent paint coatings.