

Weather Guard Exterior Wall Primer

Description

Happilac Weather Guard Exterior Wall Primer is a premium quality 100% acrylic based primer. It has a unique durability and better penetration with smooth brush-ability. It provides protection against severe conditions to all types of masonry surfaces including brickworks, plaster, wallboards and cement rendering.

Recommended For

deal for all interiors and exteriors including walls, cement renderings, plasters, wall boards, hard boards and chip boards. Make a smart choice and choose Happilac Exterior Wall Primer.

Features

- Alkali resistant
- Resists algae and fungal growth
- Tough and durable finish
- High coverage
- Eco friendly

Limitations

- Drying time may vary depending on weather and drying conditions
- Ensure the correct primer or sealers used

Product Information

| | |
|---|---|
| Certifications: VOC compliant in all regulated areas. OHSAS : 18001 ISO : 14001 ISO : 9001 | Binder type 100% Acrylic Pigment type Titanium dioxide Volume solids 48±2 % Weight solids 71±2 % Specific gravity 1.54±0.02 Odor Perfume enriched Viscosity ≤0.00 Poise Flash point Not applicable PH Slightly alkaline Application Brush, Spray Finish Matt Thinner Water Thinning As per requirement, max 30% Dries by Evaporation, Oxidation Surface dry 20-30 minutes Hard dry 2-3 hours Recoat 1.5-2 hours Drying and recoat times are temperature, humidity and film thickness dependent Film thickness (Wet) 110-120 microns per coat Film thickness (Dry) 20-30 microns per coat Coverage 16-18 m ² /liter/coat Packing 16ltr, 4 ltr, 1 ltr Storage temperature 4-33°C |
| | Technical Help: Happilac Paints technical department is always available to assist you in the correct use of our products. |
| Storage: The product must be stored in cool, dry and well ventilated space away from heat and other source of ignition. Container must be kept tightly closed and up right. | |

Surface Preparation and Application

Appropriate and good surface preparation significantly increases the top coat life and durability. Deploy skilled/experienced individuals for the application of paint. A few general instructions are given below:

New or Bare Surfaces

Surface to be painted must be dry, clean and free from all contamination. Remove dirt, grease and waxy material. Scuff with suitable sand paper, dust off and treat areas affected by mould and algae by bleaching. Prime with Happilac Weather Guard Exterior Wall Primer, dry overnight and fill surface imperfections with Happilac Exterior Wall Putty and allow the filling to dry 3-4 hours. Then apply second coat of Happilac Exterior Wall Putty and allow complete drying. Third coat is recommended for extra smoothness. Scuff the surface with appropriate scuffing paper, dust off and now substrate will be ready for further top coat application.

Previously Painted Surfaces

Remove loosely adherent old paint, clean the surface, rub with suitable sand paper to smooth the surface. Prime with Happilac Weather Guard Exterior Wall Primer, dry overnight and fill surface imperfections with Happilac Exterior Wall Putty and allow the filling to dry 3-4 hours. Then apply second coat of Happilac Exterior Wall Putty and allow complete drying. Third coat is recommended for extra smoothness. Scuff the surface with appropriate scuffing paper, dust off and now substrate will be ready for further top coat application.

| Sequence | Recommended Paint System | |
|---------------|---|--------------|
| | Recommended Product | No. of Coats |
| Sealer/Primer | Happilac Weather Guard Exterior Wall Primer | 1 |
| Putty/Filling | Happilac Exterior Wall Putty | 1-2 |
| Finish | Happilac Weather Guard | 2-3 |

Health and Safety Notes

- When applying paint, wear appropriate eye protection.
- In case of eye contact with product, rinse with plenty of water for at least 10 minutes.
- Don't breathe spray mist or dust.
- Ensure proper ventilation when applying paint.
- If swallowed, it may cause serious damage.
- When empty, don't use its container for edible storage.
- Place out of reach of the children.
- Pregnant women are advised to avoid breathing of paint mist or spray.
- In case of any emergency, undergo medical supervision as soon as possible.

WARNING: Scraping/sanding off previously painted surfaces may release lead dust or fumes. Lead is highly toxic, take protective measures thoroughly when rubbing off the old surfaces.