

Weather Guard Exterior Wall Putty

Description

Happilac Weather Guard Exterior Wall Putty is based on 100% acrylic emulsion. It is ready to use product for filling blemishes, cracks, holes on masonry surfaces and patching up surface imperfections on plastered walls. It is specially formulated for leveling of minor surface irregularities. It is recommended for both internal and external applications.

Features

- Excellent whiteness and application
- High quality and filling properties
- Fast drying and smooth finish
- Excellent abrasion resistance
- Anti fungal and antibacterial
- Ideal for interior and exterior surfaces

Recommended For

deal for all interiors and exteriors including walls, cement renderings, plasters, wall boards, hard boards and chip boards. Make a smart choice and choose Happilac Exterior Wall Putty.

Limitations

- Drying time may vary depending on weather and drying conditions.
- Ensure the correct primer or sealers used

Product Information

Certifications: VOC compliant in all regulated areas. OHSAS : 18001 ISO : 14001 ISO : 9001	Binder type 100% Acrylic Pigment type Titanium dioxide Volume solids 48±2 % Weight solids 71±2 % Specific gravity 1.61±0.05 Odor Odorless Viscosity 130±5 Poise Flash point Not applicable PH Slightly alkaline
	Application Scrapper, Spatula, Putty Knife Finish Matt Thinner Water Dries by Evaporation, Oxidation Surface dry 20-30 minutes Hard dry 24 hours Recoat 8 hours Drying and recoat times are temperature, humidity and film thickness dependent Film thickness (Wet) 120-140 microns per coat Film thickness (Dry) 35-50 microns per coat Coverage 5-7 m ² /kg/coat Packing 20kg, 5kg Storage temperature 4-33°C.
Technical Help: Happilac Paints technical department is always available to assist you in the correct use of our products.	
Storage: The product must be stored in cool, dry and well ventilated space away from heat and other source of ignition. Container must be kept tightly closed and up right.	

Surface Preparation and Application

Appropriate and good surface preparation significantly increases the top coat life and durability. Deploy skilled/experienced individuals for the application of paint. A few general instructions are given below:

New or Bare Surfaces

Surface to be painted must be dry, clean and free from all contamination. Remove dirt, grease and waxy material. Scuff with suitable sand paper, dust off and treat areas affected by mould and algae by bleaching. Prime with Happilac Weather Guard Exterior Primer, dry overnight and fill surface imperfections with Happilac Weather Guard Exterior Wall Putty and allow the filling to dry 3-4 hours. Then apply second coat of Happilac Weather Guard Exterior Wall Putty and allow complete drying. Third coat is recommended for extra smoothness. Scuff the surface with appropriate scuffing paper, dust off and now substrate will be ready for further top coat application.

Previously Painted Surfaces

Remove loosely adherent old paint, clean the surface, rub with suitable sand paper to smooth the surface. Prime with Happilac Weather Guard Exterior Primer, dry overnight and fill surface imperfections with Happilac Weather Guard Exterior Wall Putty and allow the filling to dry 3-4 hours. Then apply second coat of Happilac Weather Guard Exterior Wall Putty and allow complete drying. Third coat is recommended for extra smoothness. Scuff the surface with appropriate scuffing paper, dust off and now substrate will be ready for further top coat application.

Sequence	Recommended Paint System	
	Recommended Product	No. of Coats
Sealer	Happilac Weather Guard Exterior Primer	1
Putty/Filling	Happilac Weather Guard Exterior Wall Putty	1-2
Finish	Happilac Weather Guard	2-3

Health and Safety Notes

- When applying paint, wear appropriate eye protection.
- In case of eye contact with product, rinse with plenty of water for at least 10 minutes.
- Don't breathe spray mist or dust.
- Ensure proper ventilation when applying paint.
- If swallowed, it may cause serious damage.
- When empty, don't use its container for edible storage.
- Place out of reach of the children.
- Pregnant women are advised to avoid breathing of paint mist or spray.
- In case of any emergency, undergo medical supervision as soon as possible.

WARNING: Scraping/sanding off previously painted surfaces may release lead dust or fumes. Lead is highly toxic, take protective measures thoroughly when rubbing off the old surfaces.