

Wood Lacquer Matt

Description

Happilac Wood Lacquer Matt is a top quality matt finish for all types of wooden surfaces. It gives beautiful finish to surface coated with Wood lacquer Matt. It is ready to use product and has excellent resistance against stains and scratches.

Recommended For

Happilac Wood Lacquer Matt is highly recommended for all wood substrates including furniture, wooden case, doors and windows.

Features

- Matt finish
- Excellent resistance against stains
- Protective and decorative finish
- Nitrocellulose based

Limitations

- Drying time may vary depending on weather and drying conditions.

Product Information

Composition: Nitrocellulose binder, solvent and specialty additive.	Binder type	Nitrocellulose based
	Pigment type	N/A
Certifications: VOC compliant in all regulated areas. OHSAS : 18001 ISO : 14001 ISO : 9001	Volume solids	43±2 %
	Weight solids	60±2 %
	Specific gravity	0.94 ± 0.01
	Odor	Slight odor
	Flash Point	24°C
	Viscosity(@ Ford Cup F4)	390 ± 40Sec
	PH	Not applicable
	Application	Brush, Roller, Spray
	Thinner	Happilac NC Thinner
	Dries by	Evaporation, Oxidation
Technical Help: Happilac Paints technical department is always available to assist you in the correct use of our products.	Surface dry	10-15 mins
	Hard dry	2-3 hours
	Recoat	35-40 mins
Storage: The product must be stored in cool, dry and well ventilated place away from source of heat and ignition. Keep the container closed and upright.	Drying and recoat times are temperature, humidity and film thickness dependent	
	Film thickness	25-30 microns per coat
	Coverage	10-11 m ² /liter/coat
	Packing	3.64 ltr, 0.91 ltr
	Storage temperature	4-25 °C
	Store in cool and dry places away from ignition source	
Color	Clear	

Surface Preparation and Application

Appropriate and good surface preparation significantly increases the top coat life and durability. Deploy skilled/experienced individuals for the application of paint. A few general instructions are given below:

New or Bare Surfaces

Surface to be painted must be dry, clean and free from all contamination. Remove dirt, grease and waxy material. After surface preparation, apply 2-3 coats of Happilac Wood Sealer. Let the surface dry completely and then apply 2-3 coats of Happilac Wood Lacquer Matt.

Previously Painted Surfaces

Surface must be clean, dry and free from all defective and poorly adhering material, dirt, grease and wax. Surface must be scuffed in the direction of wood grains. After surface preparation, apply 2-3 coats of Happilac Wood Sealer. Let the surface dry completely and then apply 2-3 coats of Happilac Wood Lacquer Matt.

Health and Safety Notes

It is flammable, so keep away from combustible materials and sources of ignition e.g. oxidizing agent, strong alkaline and strong acidic material to avoid any exothermic reaction. In case of fire, use alcohol resistant foam, dry powder, AAF, CO₂, fire extinguisher. Never use water. No smoking. Keep upright and tightly closed container. Work in full ventilation. Keep out of reach of children. Harmful by inhalation so don't breathe vapor or sanding dust. Wear cartridge mask. Irritating to eyes and skin so use safety goggles, gloves and shoes. In case of contact with eyes rinse immediately with plenty of water keeping eyelids apart. Use soap and water if contacted with skin. Damage to health by prolonged exposure. Don't swallow, seek medical attention in any severe case. Take enough care during transporting, protect from heat and extreme of temperature. Store in cool and dry places. In case of accident, contain and collect spillage using sand. Don't empty into drain or water courses, very toxic to aquatic organism, dispose off any paint waste in accordance with appropriate environment quality regulation.

WARNING: Scraping/sanding off previously painted surfaces may release lead dust or fumes. Lead is highly toxic; take protective measures thoroughly when rubbing off the old surfaces.