

## Wood NC Thinner

### Description

**H**appilac Wood Care Special Thinner is a high quality, quick cutting and fast evaporating thinner specially formulated for thinning Happilac Wood Care Products. It is compatible to all wood products and retains the original properties of paint.

### Recommended For

**H**appilac Wood NC Thinner is highly recommended for all wood products.

### Features

- Compatible to all wood products
- Retains original paint properties
- Economical
- Ready to use
- Color less

### Limitations

- Drying time may vary depending on weather and drying conditions.

### Product Information

<p><b>Certifications:</b></p> <p>VOC compliant in all regulated areas. OHSAS : 18001 ISO : 14001 ISO : 9001</p>	<p><b>Composition</b> Blend of solvents and additives</p> <p><b>Pigment type</b> N/A</p> <p><b>Volume solids</b> N/A</p> <p><b>Weight solids</b> N/A</p> <p><b>Specific gravity</b> 0.79±0.01</p> <p><b>Odor</b> Slight odor</p> <p><b>Flash Point</b> 24°C</p> <p><b>Flammable</b> Yes</p> <p><b>Viscosity</b> ready to use</p> <p><b>PH</b> Not applicable</p> <p><b>Application</b> Brush, Spray</p> <p><b>Dries by</b> Evaporation, Oxidation</p> <p><b>Packing</b> 3.64 ltr, 0.91 ltr</p> <p><b>Storage temperature</b> 4-20 °C</p> <p><b>Color</b> Clear</p>
<p><b>Technical Help:</b></p> <p>Happilac Paints technical department is always available to help you in the correct use of our products.</p>	
<p><b>Storage:</b></p> <p>The product must be stored in a cool, dry and well ventilated place away from source of heat and ignition.</p>	

### Surface Preparation and Application

Appropriate and good surface preparation significantly increases the top coat life and durability. Deploy skilled/experienced individuals for the application of paint. Thin the product as recommended for specific product.

## Health and Safety Notes

It is flammable, so keep away from combustible materials and sources of ignition e.g. oxidizing agent, strong alkaline and strong acidic material to avoid any exothermic reaction. In case of fire, use alcohol resistant foam, dry powder, AAF, CO<sub>2</sub>, fire extinguisher. Never use water. No smoking. Keep upright and tightly closed container. Work in full ventilation. Keep out of reach of children. Harmful by inhalation so don't breathe vapor or sanding dust. Wear cartridge mask. Irritating to eyes and skin so use safety goggles, gloves and shoes. In case of contact with eyes rinse immediately with plenty of water keeping eyelids apart. Use soap and water if contacted with skin. Damage to health by prolonged exposure. Don't swallow, seek medical attention in any severe case. Take enough care during transporting, protect from heat and extreme of temperature. Store in cool and dry place. In case of accident, contain and collect spillage using sand. Don't empty into drain or water courses, very toxic to aquatic organism, dispose off any paint waste in accordance with appropriate environment quality regulation.

**WARNING:** Scraping/sanding off previously painted surfaces may release lead dust or fumes. Lead is highly toxic; take protective measures thoroughly when rubbing off the old surfaces.