

Epoxy Thinner

Description

Happilac Epoxy Thinner is a blend of aromatic hydrocarbon solvents, aliphatic alcohols and ketones. It is compatible to all Epoxy Paints and Primers and retains the original properties of coatings.

Recommended For

Happilac Epoxy Thinner is used for all Happilac Epoxy paints and primers.

Features

- Compatible with all epoxy paints
- Reduces drying time
- Excellent flow promoter
- Increases drying properties

Limitations

- Do not exceed the paint thinner ratio.
- Store the thinner away from source of heat.

Product Information

<p>Certifications:</p> <p>VOC compliant in all regulated areas. OHSAS : 18001 ISO : 14001 ISO : 9001</p>	<p>Composition Blend of solvents and additives</p> <p><u>Pigment type</u> N/A</p> <p><u>Volume solids</u> N/A</p> <p><u>Weight solids</u> N/A</p> <p><u>Specific gravity</u> 0.84±0.02</p> <p><u>Odor</u> Slightly odor</p> <p><u>Flash Point</u> 24°C</p> <p><u>Flammable</u> Yes</p> <p><u>Viscosity</u> ready to use</p> <p><u>Distillation Range</u> 79-144°C</p> <p><u>Residue on evaporation</u> 5mg/100mg</p> <p><u>Purity</u> 99.5%</p> <p><u>Dries by</u> Evaporation, Oxidation</p> <p><u>Packing</u> 3.64 ltr, 0.91 tr</p> <p><u>Storage temperature</u> 4-20 °C</p> <p><u>Color</u> Clear</p>
<p>Technical Help:</p> <p>Happilac Paints technical department is available to assist you in the correct use of our products.</p>	
<p>Storage:</p> <p>The product must be stored in a cool, dry and well ventilated place away source of heat and ignition. Keep the container closed and handle with care.</p>	

Storage

The product must be stored below 21°C and in accordance with national regulations. Storage conditions are to keep the containers in a dry, cool, well ventilated space and away from source of heat and ignition. Containers must be kept tightly closed.

Health and Safety Notes

- When applying paint, wear appropriate eye protection.
- In case of eye contact with product, rinse with plenty of water for at least 10 minutes.
- Don't breathe spray mist or dust.
- Ensure proper ventilation when applying paint.
- If swallowed, it may cause serious damage.
- When empty, don't use its container for edible storage.
- Place out of reach of the children.
- Pregnant women are advised to avoid breathing of paint mist or spray.
- In case of any emergency, undergo medical supervision as soon as possible.

WARNING: Scraping/sanding off previously painted surfaces may release lead dust or fumes. Lead is highly toxic; take protective measures thoroughly when rubbing off the old surfaces.