

Road Liner Thinner



Description

Happilac Road Liner Thinner is high quality paint thinner which is designed to improve the flow of Happilac Chlorinated Rubber Road Liner Paint material. It can also be used as cleaner for pumps and tools before and after painting. Happilac Road Liner Thinner is a blend of solvents, formulated to maintain the original system balance when added to the correct coating type.

RECOMMENDED USE

It is recommended to use in Happilac Chlorinated Rubber Road Liner Paint KPI-700 and Happilac Road Marking Primer.

FEATURES

- Retains original paint properties
- Fast evaporation rate
- Highly miscible with other common aromatic solvents
- Good flow and thinning properties
- Colorless

TECHNICAL & APPLICATION DATA

Certifications:	OHSAS : 18001	Composition	Blend of solvents and additives
	ISO : 14001	Weight Solids	N/A
	ISO : 9001	Specific Gravity	0.86 ± 0.01
Technical Help:	Happilac Paints technical department is always available to assist you in the correct use of our products	Odor	Pungent
		Flash Point	32°C
		PH	Not applicable
		Dries By	Evaporation, Oxidation
		Packing	20 & 3.64 Liters
		Storage Temperature	4-28°C
		Color	Clear

METHOD OF USE

Start mixing the Road Liner Thinner in the paint from the minimum quantity and add slowly while stirring. Do not overthin the paint and close the container after use.

HEALTH AND SAFETY NOTES

- Use proper PPEs (face mask, safety shoes, gloves and goggles etc.) at the time of usage
- It is flammable, so keep away from combustible materials and sources of ignition e.g. oxidizing agents, strong alkaline and strong acidic materials to avoid any exothermic reaction
- In case of fire, use alcohol resistant foam, dry powder, AAF, CO₂, fire extinguisher. Never use water
- No smoking, keep upright and tightly closed container
- Keep out of reach of children
- Harmful by inhalation so do not breathe vapor
- In case of contact with eyes rinse immediately with plenty of water keeping eyelids apart
- Use soap and water if contacted with skin
- Damage to health by prolonged exposure, do not swallow, seek medical attention in any severe case
- Take care during transportation. Protect from heat and extreme temperatures
- Store in a well-ventilated, cool and dry place in original packing away from incompatible materials
- Protect from direct sunlight
- Do not empty into drain or watercourses as it is very toxic to aquatic organisms. Dispose off any paint waste in accordance with appropriate environment quality regulations

WARNING: Scraping/sanding off previously painted surfaces may release hazardous dust or fumes which are highly toxic. Take protective measures thoroughly when rubbing off the old surfaces.

The information provided in this data sheet is accurate and authentic to the best of our knowledge and based on standard tests. However, results may vary due to possible variations in field conditions and application procedures.