

Road Liner Thinner

Description

Happilac Road Liner Thinner is a high quality thinner for multi purposes. It can be dissolved in all types of general paints like N/C Synthetic, C/R Epoxy, etc. It is mostly used for thinning the paints which are applied with the gun.

Features

- High selectivity
- Retains original paint properties
- Good flow and leveling properties
- Ready to use
- Color less

Recommended For

Happilac Road Liner Thinner is suitable for all general paints like N/C , synthetic, C/R epoxy, etc.

Limitations

- Drying time may vary depending on weather and drying conditions.

Product Information

Certifications:		Composition	Blend of solvents and additives
VOC compliant in all regulated areas.		Pigment type	N/A
OHSAS : 18001		Volume solids	N/A
ISO : 14001		Weight solids	N/A
ISO : 9001		Specific gravity	0.75± 0.010
Technical Help:		Odor	Slightly odor
Happilac Paints technical department is always available to assist you in the correct use of our products.		Flash Point	24°C
Storage:		Viscosity	ready to use
The product must be stored in cool, dry and well ventilated place away from source of heat and ignition. Keep the container closed and upright and handle with great care.		PH	Not applicable
		Application	Brush, Spray
		Dries by	Evaporation, Oxidation
		Packing	20 ltr, 3.64 ltr
		Storage temperature	4-28 °C
		Color	Clear

Method of Use

Start mixing the Road Liner Thinner in the paint from the minimum quantity and add slowly while stirring. Do not over thin the paint and close the container after use.

Health and Safety Notes

It is flammable, so keep away from combustible materials and sources of ignition e.g. oxidizing agent, strong alkaline and strong acidic material to avoid any exothermic reaction. In case of fire, use alcohol resistant foam, dry powder, AAF, CO₂, fire extinguisher. Never use water. No smoking. Keep upright and tightly closed container. Work in full ventilation. Keep out of reach of children. Harmful by inhalation so don't breathe vapor or sanding dust. Wear cartridge mask. Irritating to eyes and skin so use safety goggles, gloves and shoes, in case of contact with eyes rinse immediately with plenty of water keeping eyelids apart. Use soap and water if contacted with skin. Damage to health by prolonged exposure. Don't swallow, seek medical attention in any severe case. Take enough care during transporting, protect from heat and extreme of temperature. Store in cool and dry place. In case of accident, contain and collect spillage using sand. Don't empty into drain or water courses, very toxic to aquatic organism, dispose off any paint waste in accordance with appropriate environment quality regulation.

WARNING: Scraping/sanding off previously painted surfaces may release lead dust or fumes. Lead is highly toxic; take protective measures thoroughly when rubbing off the old surfaces.