



Happilac Paints

Description

Happilac Interior Wall Primer is a water-based PVA co-polymer primer for all types of interior masonry surfaces. It seals the powdery and porous surfaces to provide stronger adhesion of top coat.

Recommended For

Happilac Interior Wall Primer is used to seal brickwork, concrete, masonry, cement rendering and plaster etc. The Product is not suitable where the surface is saturated.

Interior Wall Primer

Features

- Excellent adhesion
- Suitable for all interior masonry surfaces
- Facilitate stronger adhesion of top coat
- Durable and high strength

Limitations

- Drying time may vary depending on weather and drying conditions.
- Ensure the correct primer is used.

Product Information	
<p>Certifications:</p> <p>OHSAS : 18001 ISO : 14001 ISO : 9001</p>	<p>Composition</p> <p>Binder : PVA Copolymer Emulsion Pigment : Lightfast non-lead pigments Solvent : Water</p> <hr/> <p>Drying Time</p> <p>Single coat at standard film thickness dependent on temperature, humidity and film thickness.</p> <p>Surface Dry / Touch Dry 20-30 minutes Recoat 1.5-2 hours Hard Dry 2-3 hours</p> <hr/> <p>Application Brush, Roller, Spray Thinner Water Thinning 10-15% or as per requirement</p> <hr/> <p>Film thickness/liter/coat</p> <p>Wet : 75-80 microns per coat Dry : 25-30 microns per coat</p> <hr/> <p>Theoretical coverage 16-18 m²/liter/coat Volume solids 40±2 % Flash point Not applicable Finish Matt</p> <hr/> <p>Cleaning</p> <p>Clean all equipment with water immediately after use.</p>
<p>Technical Help:</p> <p>Happilac Paints technical department is always available to assist you in the correct use of our products.</p>	
<p>Storage:</p> <p>The product must be stored in cool, dry and well ventilated space away from heat and other source of ignition. Container must be kept tightly closed and up right.</p>	

Surface Preparation and Application

Appropriate and good surface preparation significantly increases the top coat life and durability. Deploy skilled/experienced individuals for the application of paint. The sound preparation of substrate ensures a good key to facilitate the adhesion of subsequent coat of paint. A few general instructions are given below:

New or Bare surfaces

Surface to be painted must be dry, clean and free from all contamination. Remove dirt, grease and waxy material. Scuff the surface with suitable sand paper, dust off and apply one coat of Happilac Interior Wall Primer. Fill the surface with 2-3 coats of Happilac Strong Wall Filling and let it dry completely. Scuff the surface with suitable sand paper and dust off. Apply 2-3 coats of Happilac top coat after thinning with clean water and an interval of 1-2 hour in between coats.

Previously painted surfaces

Remove loosely adherent old paint. Scuff the surface with suitable sand paper, dust off and apply 01 coat of Happilac Interior Wall Primer. Fill surface imperfections with Happilac Strong Wall Filling and let it dry completely. Scuff the surface with suitable sand paper and dust off. Apply 2-3 coats of Happilac top coat after thinning with clean water and an interval of 1-2 hour in between coats.

Note: For best results it is **recommended to apply 1 coat of Interior Wall Primer over Strong Wall Filling** before the application of Happilac top coat.

	Recommended Paint System	No. of Coats
New or Bare Surfaces	<ul style="list-style-type: none"> ▪ Happilac Interior Wall Primer ▪ Happilac Strong Wall Filling ▪ Happilac Interior Wall Primer ▪ Happilac top coat 	1 coat 2-3 coats 1 coat 2-3 coats
Powdery Surfaces	<ul style="list-style-type: none"> ▪ Happilac Interior Wall Primer ▪ Happilac Strong Wall Filling if required ▪ Happilac Interior Wall Primer if required ▪ Happilac top coat 	1 coat 1-2 coats 1 coat 2-3 coats
Normal Sound Surfaces (Previously Painted)	<ul style="list-style-type: none"> ▪ No Primer Required ▪ Happilac top coat 	2-3 coats

**Happilac offers a good range of top coats i.e. Wall Emulsion, Special Plastic Emulsion, Matt Enamel etc. Make the smart choice and choose Happilac.*

Health and Safety Information

- When applying Paint wear suitable gloves and eye protection.
- A suitable dust mask must be worn when rubbing down.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of contact with skin, remove splashes from skin using soap and water.
- Don't breathe spray mist or dust.

- Ensure proper ventilation when applying paint.
- Harmful. If swallowed, seek medical advice.
- When empty, don't use its container for edible storage.
- Do not empty into drains or watercourses.
- Toxic to aquatic environment.
- Store in cool and dry place.
- In case of any emergency, undergo medical supervision as soon as possible.
- Keep out of the reach of children.
- Safety data sheet available for professional users on request.

The information provided in this data sheet is accurate and authentic to the best of our knowledge and based on standard tests. However results may vary due to possible variations in field conditions and application procedures.

KARSS Paint Industries (Pvt.) Ltd.
Taj colony, Millat Road Faisalabad 38050, Pakistan
Phone: +92-41 8861673, 8783444, 8581929 Fax: +92-41 8780038
info@happilacpaints.com , www.happilacpaints.com UAN: +92-41 111-00-1978