



Multi Tile Finish

Description

Happilac Multi Tile Finish is an acrylic based superior quality texture designed to make different textures for decorative purposes. It is a heavy body, and moldable texture having properties like mildew resistance and breathability.

RECOMMENDED USE

Happilac Multi Tile Finish is recommended for all types of interior and exterior masonry surfaces such as brickwork, plaster and cement rendering.

FEATURES

- Long lasting and durable
- Mildew resistant
- Acrylic based
- Moldable and adaptable

PRODUCT INFORMATION

Appearance	Texture Finish	Coverage	4-5 m ² / kg / coat
Color	Off - White		Actual spreading rate depends on film thickness applied, surface porosity, imperfections, temperature, wastage etc.
Binder Type	Acrylic copolymer		
Pigment Type	Light Fast Non-Lead Pigments		
Application	Special Multi-Tile Gun	Specific Gravity	1.68 ± 0.02
Flash Point	Not applicable	Volume Solids (Theoretical)	57 ± 2% for Off-White (other colors will vary)
Cleaning	Use clean water for all equipment immediately after use	No. of Coats	1
Thinning	Not recommended	Film Thickness	Wet: 350-450 µm / kg / coat Dry: 200-250 µm / kg / coat
		Packing	5 and 20 kg

Drying Information	5°C	15°C	25°C	35°C
Touch Dry	6 hrs	2 hrs	1 hr	0.5 hr
Hard Dry	12 hrs	6 hrs	3 hrs	1.5 hrs
Recoat	12 hrs	6 hrs	3 hrs	1.5 hrs

Drying and recoat times are dependent on temperature, humidity and film thickness.

SURFACE PREPARATION AND APPLICATION

Appropriate and good surface preparation significantly increases the top coat life and durability.

Efflorescence or mould must be treated before application of paint. Treat any area affected by mould, lichens, algae or moss with bleach.

NOTE: The information in this data sheet is not intended to be exhaustive; any person using the product for any purpose other than that specifically recommended in this data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at their own risk. All advice given or statements made about the product (whether in this data sheet or otherwise) are correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability at all for the performance of the product or for (subject to the maximum extent permitted by law) any loss or damage arising out of the use of the product. We hereby disclaim any warranties or representations, express or implied, by operation of law or otherwise, including, without limitation, any implied warranty of merchantability or fitness for a particular purpose. All products supplied and technical advice given is subject to our Conditions of Sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is liable to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to check with their local representative that this data sheet is updated prior to using the product.

Deploy skilled/experienced individuals for the application of paint. A few general instructions are given below.

NEW OR BARE SURFACES: New concrete, mortar or cement render must be allowed to cure for 8-12 weeks depending on concrete thickness and drying condition. Surface to be painted must be dry, clean and free from all contamination and efflorescent salts. Remove dirt, grease and waxy material by rubbing down using a suitable abrasive paper. Happilac Interior Wall Primer/Happilac Wall Primer Sealer. Allow the surface to dry out completely, scuff with a suitable abrasive paper, and dust off.

PREVIOUSLY PAINTED SOUND SURFACES: Scrape off all the loosely adherent and defective paint from the surface with an appropriate abrasive paper or stiff brush and dust off. Spot prime with Happilac Interior Wall Primer/Happilac Wall Primer Sealer and fill surface imperfections with Happilac Strong Wall Filling/Happilac Weatherguard Exterior Wall Putty. Allow the surface to dry out completely. Scuff with a suitable abrasive paper and dust off.

POWDERY, CRACKED AND DEFECTIVE SURFACES: Repair minor defects. Fill large holes and cracks using sand and cement mixture. Remove dirt, grease, poorly adhering and defective material from the surface by rubbing down using a stiff brush or suitable abrasive paper. Allow the surface to dry out completely and treat the surface as described above for new or bare surfaces.

FINISHING: After surface preparation, apply 1 coat of Happilac Multi-Tile Finish.

RECOMMENDED PAINT SYSTEM

Surface Type	Primer	Putty	Primer	Finish Coat
	Happilac Interior Wall Primer/Happilac Wall Primer Sealer	Happilac Strong Wall Filling/Happilac Weatherguard Exterior Wall Putty	Happilac Interior Wall Primer/Happilac Wall Primer Sealer	Happilac Multi-Tile Finish
New or Bare Surfaces	1 coat	Not Required	Not Required	1 coat
Previously Painted Sound Surfaces	Not Required	Not Required	Not Required	
Powdery, Cracked and Defective Surfaces	1 coat	Not Required	Not Required	

Consult Happilac Paints representative for the system best suited for surfaces to be painted.

HEALTH & SAFETY

- Must use goggles and gloves at the time of application
- A suitable dust mask must be worn when rubbing down
- Keep doors and windows fully open to ensure proper ventilation when applying paint
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- In case of contact with skin, remove splashes from skin using soap and water
- Do not breathe spray mist or dust
- Swallowing can result in nausea, vomiting and irritation of gastrointestinal tract
- This container is only for paint use. Do not use it for edible storage
- In the event of an accident, collect spillage using sand or earth
- Do not empty into drains or watercourses
- Toxic to aquatic environment
- Toxic by inhalation. If inhalation causes physical discomfort, move to fresh air. If discomfort persists or any breathing difficulty occurs, seek medical advice and show container label to doctor
- Keep out of reach of children
- Protect from extreme temperatures. Store in a cool and dry place
- Safety data sheet available for professional users on request

WARNING: Scraping/sanding off previously painted surfaces may release hazardous dust or fumes which are highly toxic. Take protective measures thoroughly when rubbing off the old surfaces.

The information provided in this data sheet is accurate and authentic to the best of our knowledge and based on standard tests. However, results may vary due to possible variations in field conditions and application procedures.